



NEW PRODUCT

Safety Rubber Tip

This new patent-pending Safety Rubber Tip combines OSHA compliance with a non-marring surface. The tip meets or exceeds important OSHA standards and the rubber end won't damage delicate or finished surfaces. There's no other tip like it on the market!

FEATURES AND BENEFITS

- OSHA compliant
- Non-marring so it's ideal for blowing out molds and delicate or finished surfaces
- Can be used on any of our blow guns with a standard 1/8" NPT outlet.

**Our popular
Rubber Tip is now
OSHA compliant!**

**Call Your Acme Rep or
Acme directly at:
732-432-7177**

APPLICATIONS

- For fine woodworking, molds, and automotive and industrial finishing.
- Metal finishing where a metal tip could damage the surface (i.e., auto detailing).

SPECIFICATIONS

Media Air
 Maximum working pressure: . . 150 PSI
 Maximum operating temp.: . . 175° F
 Body material: Nickel-plated brass
 Length: 1-27/64"
 Diameter:0.580"
 Weight:0.46 oz.
 Thread: 1/8-27 NPSM-2A

ORDERING INFORMATION

<i>Description</i>	<i>Model</i>
Safety Rubber Tip	A631SR
Safety Rubber Tip, display	A631SR-BL
Corresponding Acme products:	
Pistol grip blow gun	A636ST
Variable flow blow gun	A671NT
Safety blow gun	A637ST