


# GILAFLEX™

## INNER-BRAIDED PVC AIR HOSE

**NEW**



Temperature Range:  
- 40° F to +150° F  
Working Pressure:  
325 PSI @ 70° F



**SPECIAL BLEND PVC HAS NO MEMORY -**  
HOSE LAYS DOWN FLAT ON THE GROUND

**VERY TIGHT BEND RADIUS -**  
HOSE WON'T KINK & CUT OFF AIR SUPPLY

**STEEL SPRING STRAIN RELIEF -**  
PROTECTS HOSE AT ITS WEAKEST POINT (AT THE FITTING) WITHOUT INHIBITING MANEUVERABILITY

**REUSABLE FITTINGS**  
**SUPPLIED AS STANDARD -**  
MAKES FIELD REPAIR QUICK & EASY

**UV STABILIZED -**  
WON'T FADE OR DEGRADE DUE TO  
PROLONGED EXPOSURE TO LIGHT

**CHEMICAL & ABRASION RESISTANT -**  
TOUGH ENOUGH TO WITHSTAND HARSH WORKING ENVIRONMENTS

**SMOOTH OUTER COVER -**  
DOESN'T TRAP DIRT & EASY TO CLEAN

**180° BEND RADIUS**  
**WITH STRAIN RELIEF**



**TOUGH • FLEXIBLE • DURABLE • SAFE • ECONOMICAL**

### ITEM DESCRIPTION

3/8" x 25' With 1/4" MPT RIGID FITTINGS  
3/8" x 50' With 1/4" MPT RIGID FITTINGS  
3/8" x 100' With 1/4" MPT RIGID FITTINGS  
3/8" x 200' BULK (NO FITTINGS)  
3/8" x 1/4" MPT GILAFLEX RIGID REUSABLE  
FITTING, WITH STRAIN RELIEF

### MODEL NUMBER

GF60254Q  
GF60504Q  
GF61004Q  
GF6200Q  
GFRM0604SR



HB-A10



COILHOSE PNEUMATICS  
East Brunswick, NJ  
info@coilhose.com  
www.coilhose.com



ACME AUTOMOTIVE  
East Brunswick, NJ  
info@acmeautomotive.com  
www.acmeautomotive.com